

Vacuum Slurry Tankers

Running Gear, the family owned agricultural machinery manufacturer based in Ballyhaunis Co Mayo, has extended its range of spreading tanks with the introduction of the LCG slurry tanker Range. With over 50 years' experience in the manufacture of agricultural machinery, the company operates from a purpose built factory which boasts the latest in cutting, bending, welding and spraying technology.

The latest addition to their slurry tank range boasts a patented technology which significantly reduces the possibility of the tank overturning on an inclined slope or in adverse weather conditions. The new development is achieved by running an axle through an axle housing which in turn runs through the tank rather than under the tank. The main advantage of this is that centre of gravity of the tanker is lowered significantly and the tanker is more stable when cornering and when traversing inclined surfaces.



The latest innovation in vacuum tanks on the market is the 2000LCG



The Agri-Spread range of slurry tankers

LCG Features

- Lowered centre of gravity providing greater stability and safety
- Rugged construction - 6mm high quality steel with high pressure dished ends
- Capacities 2000, 2400, 2600
- 200 x 200mm heavy duty drawbar
- Braked 10 stud hubs on heavy duty commercial axle
- 10000 litre vacuum pump
- Floating ball top trap to prevent contamination of the pump
- Hydraulic opening of the rear gate valve and spring closing
- Auxillary filling points at rear and front
- Full lighting kit
- Hydraulic brakes, 6" filler and discharge points and 15ft of 6" suction hose
- An anti-corrosive primer and two coats of paint are applied to all tanks to ensure a quality long lasting finish.
- Water cyclone trap
- Adjustable Hitch
- Sprung Drawbar
- Oversize Tyres 30.5 R32

Agri-Spread Vacum Tankers - Standard Specification

Model	1300G	1600G	2000 LCG	2400 LCG	2600 LCG
Carrying Capacity	1300G / 5900L	1600G / 7300L	2000G / 9100L	2400G / 10600L	2600G / 11500L
AXLE	Single	Single	Single	Single	Single
Axle size	80mm X 80mm	90mm X 90mm	130mm x 12m	130 x 12m	130 x 12m
Vacuum Pump	8000	8000	10000	10000	10000
Length	5450mm	6100mm	6500mm	6500mm	6750mm
Width	2590mm	2590mm	2590mm	2590mm	2590mm
Height	2690mm	2845mm	2690mm	2870mm	2870mm
Unladen Weight	2150kg	2400kg	2800kg	3600kg	3900kg
Tyres	550/60 22.5	550/60 22.5	30.5 R32	30.5 R32	30.5 R32
Wheel Studs	8	8	10	10	10
Tank Thickness	6mm	6mm	6mm	6mm	6mm
Drawbar	250mm x 150mm	250mm x 150mm	200mm x 200mm	200mm x 200mm	200mm x 200mm

Optional equipment includes:

- Additional filling points
- Tankers can be galvanised.
- Hinged Back Door
- Washdown Hose Assembly with couplings
- Garda 8000/10000/12000 litre pump with raingun
- High speed running gear
- Hydraulic top fill complete with access ladder
- Hydraulic changeover on vacuum pump
- Hydraulic spinner units for control and management of water applications
- Stone trap
- Air Brakes and Air/Hydraulic Brakes
- 6" Auto coupler with Hydraulic changeover
- Sprung drawbar

For further details and optional equipment contact:

RunningGear Ltd

Coolnaha,
Ballyhaunis
Co. Mayo
Tel: 094 96 31808
Fax 09496 31525
Internet: www.agrispread.com
email: sales@agrispread.com

Agri-Spread® is a registered trade mark of Running Gear Ltd

UK Office

Running Gear Ltd
Allendale, Hexham
Northumberland
NE47 9PY
Tel: 0143 4683626
Mobile: 07780928560
www.dalesagrisalesagency.co.uk
Email: halliday@aol.com.